



**M|B|I**  
M. BRASHEM, INC.

14023 NE 8th Street  
Bellevue, WA 98007, USA  
**Phone:** 1-425-641-1566  
**Toll Free:** 1-800-274-2008  
**Fax:** 1-425-641-1583  
**E-mail:** info@mbigraphite.com

Quality Engineered Graphite  
Technical Bulletin

**GRADE MBEDM-31**

Is a quality, fine grain, high strength isostatically molded graphite that can be machined to tight tolerances and used in a vast array of the most difficult applications.

**TYPICAL APPLICATIONS INCLUDE:**

Continuous casting dies, semiconductor and composite parts, sintering (ceramic and electronic), hot pressing, diamond drill bits and rocket nozzles.

**SIZES**

Available upon request.

**TYPICAL PROPERTIES @ ROOM TEMPERATURE (ENGLISH)**

Bulk Density (g/cm <sup>3</sup> )	1.80
Average Particle Size (in.)	.001
Specific Resistance (10 <sup>-4</sup> Ω.in)	5.91
Flexural Strength (psi)	6,105
CTE (10 <sup>-6</sup> /°F)	2.5
Ash Content (%/nppm)	.10/1000
Young's Modulus (x10 <sup>-6</sup> /psi)	1.7
Compressive Strength (psi)	12,501
Hardness (shore)	55

\*Note: This information is not a warranty. It is offered solely for your consideration, investigation and verification.

**"GRAPHITE IS OUR SPECIALTY"**

Phone: 1-800-274-2008

www.mbigraphite.com

Fax: 1-425-641-1583